

L-BRACKET TYPE DL06 DOUBLE UP AND DOWN

L-BRACKET DOUBLE UP AND DOWN TYPE DL06

Materials SS304, SS316, SS316L, SS316TI, S235JR-MG, S235JR-HDG
50°C 24h average temperature Standard it

Item No .	T	A	B	C	H	L	K	Slot
DL06-120.50.30.3	3	120	50	30	15	A/2	A/4	8.5 x 22
DL06-120.50.35.3	3	120	50	35	15	A/2	A/4	8.5 x 22
DL06-120.50.40.3	3	120	50	40	15	A/2	A/4	8.5 x 22
DL06-140.60.30.3	3	140	60	30	15	A/2	A/4	8.5 x 22
DL06-140.50.45.3	3	140	50	45	15	A/2	A/4	8.5 x 22
DL06-120.60.30.4	4	120	60	30	15	A/2	A/4	8.5 x 22
DL06-120.60.35.4	4	120	60	35	15	A/2	A/4	8.5 x 22
DL06-120.50.40.4	4	120	50	40	15	A/2	A/4	10.5 x 22
DL06-120.50.45.4	4	120	50	45	15	A/2	A/4	10.5 x 22
DL06-120.50.50.4	4	120	50	50	15	A/2	A/4	8.5 x 22
DL06-120.60.50.4	4	120	60	50	15	A/2	A/4	10.5 x 22
DL06-140.60.50.4	4	140	60	50	15	A/2	A/4	10.5 x 22

$L = A/2$ $K = A/4$

